



GB	Declaration of Performance	DoP – No.	01-01-02-10-S-23-294D-K
----	----------------------------	-----------	-------------------------

1. **Unique identification code of the product-type:** 4066633036096
2. **Intended Use:** For structural timber products
3. **Manufacturer:** suki.international GmbH, Suki-Straße 1, 54526 Landscheid, Germany
4. **Authorised representative:** N/A
5. **System of Assessment:** System 3
6. **Harmonized Standard and Notified Body:**  
EN 14592:2008+A1:2012, System 3; Type testing (ITT) made by Notified Body: HFB Engineering GmbH, Zschortauer Straße 42, 04129 Leipzig, Germany, Identification Number (NB 1034)
7. **European Technical assessment and Assessment Body:** N/A
8. **Declared Performance:**

Essential characteristics	Unit	Performance	Harmonized technical Specification
Characteristic Yield Moment M <sub>y,k</sub>	Nm	2,60	EN 14592:2008+A1:2012
Characteristic Tensile Capacity f <sub>tens,k</sub>	kN	4,19	EN 14592:2008+A1:2012
Characteristic Withdrawal Parameter f <sub>ax,k</sub> Characteristic wood density ρ <sub>k</sub>	N/mm <sup>2</sup> Kg/m <sup>3</sup>	14,0 402	EN 14592:2008+A1:2012
Characteristic Head Pull Through Parameter f <sub>head,k</sub> Characteristic wood density ρ <sub>k</sub>	N/mm <sup>2</sup> Kg/m <sup>3</sup>	11,12 511	EN 14592:2008+A1:2012
Characteristic torsion ratio F <sub>tor, k</sub> /R <sub>tor, k</sub>	Nm	>1,5	EN 14592:2008+A1:2012
Durability		Class 3 according to EN 1995-1-1, austenitic stainless steel according to EN 10088-3	EN 14592:2008+A1:2012

9. The performance of the product identified above is in conformity with the set of declared performance/s.  
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Johann Padura  
Quality Assurance

Landscheid, 18.12.2023

**suki.international GmbH**  
Suki-Straße 1  
D-54526 Landscheid  
Tel./Fon: +49 (0)-6575/71-0  
www.suki.de